



LRP LED Lamp



Solais LED LRP Lamp Replacement



LRP38



LRP30LN

Product Description: Solais Lighting's newest family of LED lamps offers a unique replacement solution for traditional lighting sources – providing the incandescent performance, light output and aesthetics with our recessed OPTICS² patent-pending technology.

Performance Summary: Fully dimmable / Halogen PAR form factor (ANSI-compliant) / Lightest LED lamps on the market / Certified to UL Standard 1993 / RoHS-compliant / Contain no lead or mercury

Applications: Designed for use in track and recessed fixtures.

OPTICS² Technology: Optics Squared technology is a patent-pending system in Solais LED passive lamps that incorporates a primary recessed and secondary surface dual-optic process, which allows Solais to duplicate the performance and aesthetics of incandescent light sources.

LRP38	/ 25	/ 30K
Form Factor PAR38	Beam Angle 25 Degrees	CCT 3000K



Product Code	Power (Watts)	Beam Angle	CCT (K)	Lumen Output	CBCP (cd)	CRI	Power Factor	Base Type	Weight (oz.)	Length (in.)	Diam. (in.)	Dim.	ENERGY STAR®
LRP38													
LRP38/25/30K	16	25	3000	1025	3,950	85	.92	E26	9.4	5.3	4.9	Yes	
LRP38/40/30K	16	40	3000	950	1,500	85	.92	E26	9.4	5.3	4.9	Yes	
LRP38/25/27K	16	25	2700	975	3,750	85	.92	E26	9.4	5.3	4.9	Yes	
LRP38/40/27K	16	40	2700	900	1,450	85	.92	E26	9.4	5.3	4.9	Yes	
LRP30LN													
LRP30LN/25/30K	14	25	3000	900	3,000	85	.92	E26	7.7	4.5	3.9	Yes	
LRP30LN/40/30K	14	40	3000	850	1,350	85	.92	E26	7.7	4.5	3.9	Yes	
LRP30LN/25/27K	14	25	2700	850	2,800	85	.92	E26	7.7	4.5	3.9	Yes	
LRP30LN/40/27K	14	40	2700	800	1,250	85	.92	E26	7.7	4.5	3.9	Yes	

LIMITED WARRANTY: Solais Lighting warrants that our lamps and fixtures will operate for a period of five (5) years from the date of purchase or 25,000 hours, whichever comes first, when used in accordance with package and lamp directions. If your Solais product does not last for the warranty period, please send your name and address, the product you are returning, register receipts and proof of purchase to the address listed on our website. This limited warranty does not cover products subject to misuse, electrical current fluctuation, accident, neglect, or acts of God. THIS REPLACEMENT OR REPAIR IS THE SOLE WARRANTY OBLIGATION OF SOLAIS AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES EXCLUDED.

For complete warranty terms and conditions, please see: www.solais.com/warranty

WARNING: Not for use in fully enclosed luminaires. Risk of electric shock. Suitable for DAMP locations. NOT FOR USE WHEN EXPOSED TO THE WEATHER. This device is not intended for use with emergency exit fixtures or emergency exit lights. May not be compatible with all dimmers; please visit solais.com/dimming for up-to-date dimmer compatibility information.

NOTES: This device complies with Part 15 of the FCC Rule. This product may cause interference with other devices. If interference occurs, change the locations of the products involved. **Compatible on 120v systems.**